(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property **Organization** International Bureau





(43) International Publication Date 16 December 2004 (16.12.2004)

PCT

(10) International Publication Number WO 2004/109527 A1

(51) International Patent Classification7: G01R 31/28

G06F 13/00.

(21) International Application Number:

PCT/US2004/017461

(22) International Filing Date:

3 June 2004 (03.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003-158091


3 June 2003 (03.06.2003)

- (71) Applicant (for all designated States except US): AGI-LENT TECHNOLOGIES, INC. [US/US]; 395 Page Mill Road, P.O. Box 10395, Palo Alto, CA 94303-0870 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): HARADA, Koji [JP/JP]; 32-12, Tainohata-Minami, Suma-Ku, Kobe-Shi, Hyogo 654-0132 (JP).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments



generating modulated signals (140) based on demodulated data and setting data supplied in advance, outputting the modulated signals as reference signals, and analyzing (150) the network properties of the device under test (20) by comparing or referencing the output signals of the device under test and these reference signals.

